



SAFETY PRODUCTS



GANDHI
Automations Pvt Ltd

India's **No.1** Entrance Automation & Loading Bay Equipment Company

Motorised Wheel Block System




An integral sensor in the wheel block accurately determines the position of the rearmost wheel, where upon the wheel block is automatically extended and the wheel is restrained.

The most sophisticated electrical hydraulic technology, operated via PLC and is controlled using a button on the control panel in the building. An integral sensor in the wheel block accurately determines the position of the rear most wheel, whereupon the wheel block is automatically extended and the wheel is restrained. The restraint process occurs in approx. 30 seconds regardless of the size and position of the wheel.

- The wheel block applies constant pressure against the wheel to prevent the vehicle from creeping forwards.
- Integrated wheel guides.
- Complete electrical hydraulic operation controlled via PLC.
- An acoustic alarm and warning lights are in being positioned.
- In addition; an external red/green traffic light ensures clear communication.
- Emergency release possible at all times.

Diagram



Gandhi Automations standard Motorised Wheel Block System is suitable for all types and size of trailer and trucks. Different types of wheel guides are available. These wheel guides will guide the vehicle for the perfect parking. This makes the Wheel Block a system which is extremely versatile. And it is easy to install on the ground.



Traffic Light



Wheel Guides



Acoustic Alarm

Wheel guides are hot dipped galvanized steel guides consisting of two round shaped pipes. Fixed on court pavement to grant perfect docking. While the wheel block is in operation the warning lights and alarms are in constant working.

The external red/green traffic light ensures clear indication. Once the wheel block's operation is done traffic light will become green and the driver will get the indication to move the vehicle.




Manual Wheel Block System

The wedge is put under a vehicle wheel, as to restrain its movement, which increases the safety-on-work.

- Heavy duty type, with rudder and positioning wheels
- Construction heavy duty rigid plastic component sandwich side covered with stainless steel plates, blocked by passing through tyres

Safety Truck Lock



The manual and motorised safety truck lock series is a low profile, non-impact design vehicle restraint featuring the Hydraulic / Mechanical floating system, a large spring-loaded barrier that automatically adjusts to various truck heights, maintaining positive contact during loading operations at all times.

Both Motorised and manual model can secure trailer with over 14.5 tons of restraining force. The barrier housing stores at only 225mm above grade, staying clear of incoming trucks, and has a vertical working range of 760mm above grade to safely engage even that highest of rear impact guards.

Gandhi Motorised & Manual Safety truck lock are designed to provide the highest level of safety based on your application. Safety truck lock are the only truck resistance in the industry that provide full-time communication of the lock's engagement status to the forklift driver.

Gandhi Motorised and manual truck lock offers the best protection against all type of trailer separation accidents dock lock are designed for impact and to withstand the loading dock environment while also featuring the most universal hook widest operating range enhanced track and stronger slope extension.

A loading dock separation accident is one in which a truck moves away from the dock while a forklift operator is unloading or loading the truck. Loading dock separation accidents can cause serious, long-term injuries or, even worse, fatalities for forklift operators.

There are extremely common kinds of loading dock separation accident like Early Departure, trailer creep, Trailer tip over etc that can happen, but preventative safety measures can minimize the risk of them happening in your facility.

Full time protection, full time communication only with Gandhi Motorised and manual safety truck lock.

MANUAL SAFETY TRUCK LOCK

MOTORISED SAFETY TRUCK LOCK



Control Card



Traffic Light



Control Card

- Non-Impact Design
- Barrier Stores 225mm high to Escape impact from low rear impact guards
- Barrier Sensor Communicates Positive Lock Position
- Barrier Automatically Adjusts to Truck Movement During Loading
- Vertical locking hook secures virtually all rear impact guards with in excess of 14.5 Tons of Restraining Force
- Easy to Install and Simple to Operate
- IP66 Control card enclosure
- Self Cleaning Guide Track
- Vertical Operating Range from 225mm to 760mm
- Easy to Install & Simple to Operate
- Inside and Outside Traffic Lights for Loading and unloading communication
- Virtually No Required Maintenance
- Housing Encloses Working Parts From Inclement Weather and Debris
- All Weather Hot Dip Galvanised components for Superior Durability
- Mounting Force in Excess of 45 Tons

Product application and specification





Motorised Safety Truck Lock Operation

The trailer is backed into position at the loading dock leveler until contacting the dock bumpers. The driver sets the brakes and chocks the wheels. The dock attendant pushes a control button that activates the safety truck lock barrier that will rise in the vertical track until contacting the rear impact guard and securing the trailer to the loading dock leveler. An override selector button will allow a bypass operation of the dock leveler while maintaining a red external signal light. The barrier provides a restraining force in excess of 14.5 tons. Adjusting automatically to trailer float during loading and unloading ensuring the trailer is fully restrained at all times. When loading/unloading is completed the dock attendant stores the barrier using the release button.

Manual Safety Truck Lock Operation


The trailer is backed into position at the loading dock leveler until contacting the dock bumpers. The driver sets the brakes and chocks the wheels. The dock attendant using the control bar activates the safety truck lock barrier that will rise in the vertical track until contacting the rear impact guard and securing the trailer to the loading dock leveler. The barrier provides a restraining force in excess of 14.5 tons.

Adjusting automatically to trailer float during loading and unloading ensuring trailer is fully restrained at all times. The restraint monitors for abnormal conditions and indicates it is unsafe to load with an inside red light if the rear impact guard is not detected. An override control is provided for use after a proper lock is determined by the dock attendant.

Communication

Safety equipment includes flashing red or green inside and outside lights, operator instructions and outside mounted sign with forward and reverse lettering for truck driver.

Product Dimension



Retractable Dock Safety Barrier



Help prevent loading dock accidents



Helps prevent fork trucks, pallet jacks, and pedestrians from falling off a loading dock

Helps protect the dangerous 1200mm drop off at the loading dock that can result in serious injuries that are sometimes fatal

Dock Safety Barrier is simple & easy to use safety solution for almost any loading dock. It has ability to help to prevent the serious life threatening accident.

The Retractable Dock Safety Barrier is designed to stop up to 13636 Kg (Refer impact rating chart for complete weight and speed ratings)

Retractable Dock Safety Barrier is made-up of bright black mesh curtain of height 1150mm with three heavy duty restraint strip. It also serves as a highly visible warning for operators and pedestrians.

It consist of two heavy duty 1200mm high orange warden guards anchored on either side of clear opening, which provides excellent door track protection. During loading or unloading, the dock safety barrier retracts into one of the wardens.

It's operated manually and easily fits across opening up to 5000mm wide

Gandhi Dock Safety Barriers Provide Full-time safety integration for Full time Protection

The Dock Safety Barrier is designed to interlocked with any loading bay equipment system (like Sectional Doors, Dock Levelers & Vehicle Restraint System and other existing loading bay equipment) to ensure full time loading dock safety.



1 The red light on the traffic light inside building indicates that the Dock Safety Barrier is locked safely across the opening.



2 The Vehicle Restraint System safely secures the trailer to the loading dock.



3 When Vehicle Restraint System securely connects the vehicle, the inside traffic light turns green, the dock safety barrier interlock releases, allowing for loading and unloading of a trailer.

Impact Rating Chart Retractable Dock Safety Barrier

Mass (kg)			3000	4000	4545	5000	6000	6818	7000	8000	9091	10000	11364	12000	13000	13636
MPH	Km/hr	M/s	Kinetic Energy (Joules)													
2	3.2	0.89	1195	1593	1810	1991	2389	2715	2787	3186	3620	3982	4525	4778	5176	5430
2.5	4	1.12	1867	2489	2828	3111	3733	4242	4355	4977	5656	6222	7070	7466	8088	8484
3	4.8	1.34	2688	3584	4072	4480	5376	6109	6271	7167	8145	8959	10181	10751	11647	12217
3.5	5.6	1.56	3658	4878	5543	6097	7317	8314	8536	9756	11086	12195	13857	14633	15853	16629
4	6.4	1.78	4778	6371	7240	7964	9557	10860	11149	12742	14480	15928	18099	19113	20706	21719
4.5	7.2	2.01	6047	8063	9163	10079	12095	13744	14111	16127	18326	20158	22907	24190	26206	27489
5	8	2.23	7466	9955	11312	12443	14932	16968	17421	19909	22624	24887	28280	29864	32353	33937
5.5	8.8	2.45	9034	12045	13688	15057	18068	20532	21079	24090	27375	30113	34219	36136	39147	41063
6	9.6	2.68	10751	14335	16290	17918	21502	24434	25086	28670	32579	35837	40724	43004	46588	48869
6.5	10.4	2.9	12618	16823	19118	21029	25235	28676	29441	33647	38235	42059	47794	50470	54676	57353
7	11.2	3.13	14633	19511	22172	24389	29267	33258	34145	39023	44344	48778	55430	58534	63412	66516

- Will absorb multiple impact at this level minimal damage
- Will absorb an impact, may sustain damage
- Will not absorb an impact this level

The barrier load and speed test (Chart expresses an impact rating in term of kinetic energy)

SafetyKeeper



The SafetyKeeper is a twin barrier that makes elevated platform loading and unloading safer. It ensures full time safety at the edge of a mezzanine platform by keeping one entry closed at all times.

As per ANSI standard, there must be full-time protection when loading and unloading materials from an elevated platform. Industrial mezzanines must have handrails and gates around all edges however, these gates need to be opened from time-to-time to accommodate the loading and unloading process. Gandhi Automations offers the safety barrier solutions, the Safetykeeper.

Safe & Efficient

Safety challenges exist around every corner of industrial facilities, from forklifts zipping around workers and materials to hazardous machining processes that need to be guarded.

Safety barriers are typically used to separate workers and pedestrians from potentially hazardous operations or dangerous situations. They play an important role in helping industrial facilities operate safely and efficiently.

Multi-level environments create a number of advantages and efficiencies for companies but there are areas of concern that must be protected. Unprotected mezzanines or multi-level environments pose a high risk for employee related falls.

Space Utilizer

Nowadays as companies utilize their existing space maximum within their facilities, many are turning to mezzanines, elevated work platforms or multi-level work environments to create additional storage space or work areas for employees.

Controlled Access Areas

Installed on the edge where pallet loads from the floor level are regularly deposited for pick-up, the gate features a reciprocating barrier that is interconnected and can't be opened at the same time. When the outer gate opens to allow pallets to enter the mezzanine level, the inner gate automatically closes, keeping workers out.

Features

- Steel side frames provide built-in track protection
- Footrail / toe-edge prevents material from unintentionally being pushed from an elevated space to a lower level
- Exclusive design ensures that both gates work in unity
- Safe-T-Latch prevents an individual from raising the gate from inside the work zone, helping prevent an employee from falling from the mezzanine while working the load
- Galvanised track and nylon rollers provide for smooth operation
- Available in manual and automatic version





STAR EXPORT HOUSE
(Government of India Recognised)



ISO 9001 : 2015, ISO 14001 : 2015
ISO 45001 : 2018

Gandhi Automations operates a policy of continuous development and reserves the right to make technical modifications / replacements without prior notice.



Automations Pvt Ltd

India's No.1 Entrance Automation & Loading Bay Equipment Company

CORPORATE OFFICE

Chawda Commercial Centre, Link Road, Malad (W), Mumbai-400064, India

Tel : +91 22 6672 0200 / 6672 0300 (200 Lines)

Fax : +91 22 6672 0201

Email : sales@geapl.co.in

Website: www.geapl.co.in



TOLL FREE

1800 209 0200

From Anywhere in India

Ahmedabad - 93273 01555
Bengaluru - 93435 09090
Bhopal - 93292 94939
Bhubaneswar - 93385 69889
Chandigarh - 93176 41324
Chennai - 93809 31777
Coimbatore - 93452 99944
Goa - 93731 37970
Guwahati - 93248 98159

Hyderabad - 93473 75737
Indore - 93034 64410
Jaipur - 93520 41024
Jamshedpur - 93219 76556
Kochi - 93882 04774
Kolkata - 93300 60855
Lucknow - 93055 67760
Mangalore - 93797 41352
Nagpur - 93250 45410

New Delhi - 93131 99044
Patna - 93219 76557
Pune - 93245 30710
Raipur - 93524 40068
Ranchi - 93044 95570
Surat - 93270 97410
Vadodara - 93756 41357
Visakhapatnam - 93463 34102